



Natural Oil Woodstain Effect

Binding agents

- Based on the renewable plant raw materials: sunflower oil, soya oil, thistle oil and linseed oil

Solvents

- Aliphatic hydrocarbons = dearomatized white spirit (benzene-free)

Pigments

- Effect Pigments
- Mineral pigments on the basis of ore; titanium dioxide and iron oxides (yellow, red, brown, black)
- Organic pigments (yellow, red, green, blue) which are in compliance with German Industrial Norm DIN 53160 (fast to perspiration and saliva) and Euro Norm EN 71.3 (safety of children's toys)

Earth

- Mineral origin, silica sand, dolomite and swelling clays (argillaceous rock)

The used mineral pigments and earths have been purified from all poisonous ingredients (e.g. heavy metals) and are physiologically safe.

Additives

- Siccatives (are obtained from the respective minerals and are lead-free)
- Ketoximes
- Polysiloxanes (on basis of silicic acid)

The listed ingredients serve to regulate the drying process and to prevent film formation (5 years storage stability) and as a strong water repellent.

Active ingredient (film protection)

- Propiconazole.

Osmo Natural Oil Woodstain contains active agents to protect the coating against algae and fungus attack.

Further details concerning technical characteristics etc. can be obtained from the respective product information.

*The above mentioned information is provided to the best of our knowledge however without any liability.
(Version 10/2015)*